

Nitron 16

Art no: RX-RNF2016



Rubberex™



Art no:	RX-RNF2016
Size:	8-11
Materials:	Nitrile
Packaging:	3/36
Standard:	EN420, EN388:2016, EN374-1:2016, EN374-5:2016
Category:	III



CATEGORY: III



EN388:2016



4101X

EN374-1
TYPE A



AJLOPTK

EN374-5



Properties

Longer chemical protection glove in premium grade nitrile rubber with excellent resistance against fats, aromatic and petroleum based solvents. Raised diamond pattern in the palm for increased grip in both wet and oily environments. Cotton flocklined interior for comfort. Food handling approved. Length (mm): 410 +/- 10, Thickness (mm): 0.52 +/- 0.03

Material information

Length (mm): 410 +/- 10, Thickness (mm): 0.52 +/- 0.03, Material: Nitrile

How to read the pictogram:

Technical facts: Intermediate design (category II)

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se