

PRODUCT DATA SHEET



Hermes Art no: C-7095



Art no:	C-7095
Size:	8-12
Material:	Cowsplit, cowgrain, cotton fleece, Kevlar® thread
Packaging:	6/36
Standard:	EN ISO 21420:2020, EN12477:2001, EN388:2019, EN407:2020
Category:	II



EN12477+A1
TYPE B

CATEGORY: II



2133X



412X4X



Properties

Robust welding glove made from durable yet flexible premium cowgrain leather, with the back and cuff made of cowsplit. Lined with a cotton fleece lining. The glove is stitched with strong, heat-resistant Kevlar® thread with double seams in exposed areas. Extra reinforcements on both the thumb grip and the entire index finger for increased durability. An elastic seam around the wrist ensures the glove fits better and more securely on the hand.

Material information

The gloves are sewn in cowgrain and cowsplit leather. Lining inside the hand with cotton fleece. All seams in Kevlar® thread.

How to read the pictogram:

Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



a b c d e f

Abrasion resistance
Cut resistance
Tear resistance
Puncture resistance
Extended cut resistance
Impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se