

Hyperguard PU

Art no: HV-PE363



Art no:	HV-PE363
Size:	7-12
Materials:	Dyneema® PU
Packaging:	12/120
Standard:	EN420, EN388:2016
Category:	II



EN388:2016



CATEGORY: II

4X42B



Properties

Knitted cut resistant glove (Level B) in white Dyneema® for a high dexterity glove with great tactile sensitivity. Extremely thin PU coating that still gives good abrasion resistance as well as a firm grip. The ergonomic design of the liner makes the glove very comfortable and reduces finger fatigue.

Material information

Knitted cut protection glove made of Dyneema (Level B). Durable PU coating in the inner hand.

Technical facts: Intermediate design (category II)


How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)



For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.