

PRODUCT DATA SHEET



Sofcut C

Art no: HV-LX3231



Art no:	HV-LX3231
Size:	6/XS-12/3XL
Materials:	HPPE/Steel, Polyester/Spandex, Latex
Packaging:	12/120
Standard:	EN ISO 21420:2020, EN388:2016, EN407:2020
Category:	II



CATEGORY: II



EN388:2016



3X42C

EN407:2020



X1XXXX



Properties

Knitted orange cut-resistant glove (Level C) in polyester/spandex and HPPE reinforced with steel. The glove is very flexible with a great fit and exceptional tactile sensitivity. Black latex coating for an exceptional grip especially in wet conditions. Butadiene free. The ergonomic design of the glove give advantages such as comfort and less hand fatigue.

Material information

Knitted in 13 gauge HPPE/ Steel (cut-resistance level C), polyester/spandex with latex coating.

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se