

Oiltouch

Art no: HV-NKD5001



Art no:	HV-NKD5001
Size:	6/XS-12/3XL
Materials:	Nylon, Nitrile
Packaging:	12/120
Standard:	EN ISO 21420:2020, EN388:2016
Category:	II



CATEGORY: II



EN388:2016



4131X



Properties

Knitted waterproof glove in nylon with superior fit and comfort even for long time use. Double nitrile coating makes the glove waterproof with excellent oil-resistant features. Butadiene free. Outer layer in a smooth nitrile coating with a great grip in dry, wet and oily conditions. Extremely light glove suitable for wet and oily environments with high requirements on a safe grip and long term usage.

Material information

Knitted in 15 gauge double layers of nitrile coating.

Technical facts: Intermediate design (category II)

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance ————
 cut resistance ————
 tear resistance ————
 puncture resistance ————
 extended cut resistance ————
 impact protection (optional) ————

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.