

PRODUCT DATA SHEET



Gentle Grip Orange

Art no: RX-84ORG-DP



Rubberex™



Art no:	RX-84ORG-DP
Size:	S-XL
Materials:	Nitrile
Packaging:	S-XL: 1 (100 pcs)/10 (1000 pcs)
Standard:	EN420, EN374-1:2016, EN374-5:2016
Category:	III



CATEGORY: III



EN374-1
TYPE B



KTP

EN374-5



VIRUS



AQL

1.5%

Properties

Special thickness disposable gloves in durable orange nitrile with high visibility. Raised diamond grip pattern for better grip. Powder free and silicone free. Ergonomically designed for perfect fit and higher sensitivity. Good chemical resistance, especially against oil, grease and petroleum-based chemicals. Approved for food stuff handling. Recommended for individuals with latex protein allergies. Length (mm): 240 +/- 10, Thickness (mm): 0.21 +/- 0.02, Weight (g) per pc.: 8.4 +/- 0.2

Material information

Made from 100% nitrile .Length (mm): 240 +/- 10, Thickness (mm): 0.21 +/- 0.02, Weight (g) per pair: 8.4 +/- 0.2

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se