

PRODUCT DATA SHEET



Vulcanos Art no: C-7000FL



Art no:	C-7000FL
Size:	8-11
Material:	Cow split, cotton denim, cotton fleece, Kevlar® thread
Packaging:	6/36
Standard:	EN ISO 21420:2020, EN12477:2001, EN388:2019, EN407:2020
Category:	II



EN12477+A1
TYPE A

CATEGORY: II



3243X



412X4X



Properties

Fully lined welding glove made entirely of high-quality cow split leather. The glove is sewn with strong and heat-resistant Kevlar® thread, with double stitching in exposed areas. Extra reinforcements with welted seams in both the thumb grip and the entire index finger for increased durability. Fleece lining in the palm and cotton denim lining in the cuff. A straight, classic design with a sturdy elastic seam at the wrist for a better fit.

Material information

The gloves are sewn in cow split leather. Lining in the cuff with cotton denim and inside the hand with cotton fleece. All seams in Kevlar® thread.

Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:



a b c d e f

Abrasion resistance
Cut resistance
Tear resistance
Puncture resistance
Extended cut resistance
Impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se