

PRODUCT DATA SHEET



Air Winter 5213

Art no: HV-T-5213



NXG



| | |
|------------|-----------------------------------|
| Art no: | HV-T-5213 |
| Size: | 8-11 |
| Material: | Polyester, Acrylic, Nitrile |
| Packaging: | 12/120 |
| Standard: | EN ISO 21420:2020, EN388:2016, |
| Category: | EN407:2020, EN511:2007 |
| | II |



CAT: II



EN388



3121X

EN407



X1XXXX

EN511



X2X



Properties

Seamless knitted winter glove with lining – 15-gauge polyester in hi-vis orange on the outside and brushed 10-gauge acrylic on the inside – providing warmth and flexibility in cold environments. The palm is coated with foamed nitrile and nitrile dots for excellent grip and durability in damp or slightly oily conditions. The brushed acrylic lining insulates effectively without compromising dexterity or comfort.

Material information

The glove is knitted with a 15 Gauge machine which means 15 stitches per inch. The thread is in polyester and coated in foamed nitrile in the palm and over the fingers. Inside the glove is a 10 gauge liner in acrylic.

How to read the pictogram:

Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



a b c d e f

Abrasion resistance
Cut resistance
Tear resistance
Puncture resistance
Extended cut resistance
Impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se