

Tuffalene® glove

Art no: AD-11



Art no:	AD-11
Size:	S-XXL
Materials:	Tuffalene® fibre, PU
Packaging:	12/120
Standard:	EN420, EN388:2016
Category:	II



CATEGORY: II



EN388:2016



3241A



Properties

Cut resistant glove (Level A) in Tuffalene® fibre. PU dipped in the palm and up over the fingertips for a secure grip. Thin, flexible and incredibly durable. Excellent choice when working with glass or metal objects with sharp edges. Very popular among construction workers. The glove is knitted with a single thread and has no seams.

Material information

Handskarna är stickade i "13 Gauge" maskiner vilket innebär 13 maskor/tum.
Tråden innehåller: Tuffalene 78% +/- 7% Lycra 10% +/- 3% Other 12% +/- 3%

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)