

PRODUCT DATA SHEET



Extreme

Art no: S-991



Art no:	S-991
Size:	6-11
Material:	Amara, Polyester
Packaging:	12/120
Standard:	EN ISO 21420:2020, EN388:2019
Category:	II



EN388



CATEGORY: II

2121X



Properties

Assembly glove in Amara with better breathability than most leather gloves. The upper hand in polyester. Velcro lock for a better and safer fit. Recommended especially for people who are allergic to chromium. The glove is particularly suitable when assembling and packing jobs.

Material information

The gloves are sewn in Amara, upper hand in polyester.

How to read the pictogram:

Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



a b c d e f

Abrasion resistance
Cut resistance
Tear resistance
Puncture resistance
Extended cut resistance
Impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se