

# PRODUCT DATA SHEET



## Heavaprene

Art no: RX-HP300



Rubberex™



Art no:	RX-HP300
Size:	S-XXXL
Materials:	Latex, Neoprene
Packaging:	12/144
Standard:	EN420, EN388:2016, EN374-1:2016, EN374-5:2016
Category:	III



CATEGORY: III



EN388:2016



3111X

EN374-1  
TYPE A



AKLNPT

EN374-5



VIRUS



## Properties

Chemical protection glove in triple layer rubber. Slightly thicker for greater abrasion and chemical resistance, primarily against oils and fats. Excellent grip in both wet and oily conditions. Cotton flocklined interior for comfort. Food handling approved. Length (mm): 320 +/- 10, Thickness (mm): 0.7 +/- 0.03

## Material information

Length (mm): 320 +/- 10, Thickness (mm): 0.7 +/- 0.03. Materials: Latex, Polychloroprene

## Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance  
cut resistance  
tear resistance  
puncture resistance  
extended cut resistance  
impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se