

PRODUCT DATA SHEET



Super Neoprene

Art no: RX-NEO400



Rubberex™



Art no:	RX-NEO400
Size:	S-XXXL
Materials:	Latex, Neoprene
Packaging:	12/144
Standard:	EN420, EN388:2016, EN374-1:2016, EN374-5:2016
Category:	III



CATEGORY: III



EN388:2016



2111X

EN374-1
TYPE A



BKLOPT

EN374-5



VIRUS



Properties

Heavy duty chemical protection glove in neoprene rubber for industrial use. Excellent durability and resistance against most solvents, mild acids, fats and oils. Cotton flocklined interior for comfort. Food handling approved. Length (mm): 330 +/- 10, Thickness (mm): 0.68 +/- 0.03

Material information

Length (mm): 330 +/- 10, Thickness (mm): 0.68 +/- 0.03, Materials: Latex, Polychloroprene, Neopren

How to read the pictogram:

Technical facts: Intermediate design (category II)

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se