

## Super Nitrile 15

Art no: RX-RNF15G



**Rubberex™**



Art no:	RX-RNF15G
Size:	S-XXXL
Materials:	Nitrile
Packaging:	12/144
Standard:	EN420, EN388:2016, EN374-1:2016, EN374-5:2016
Category:	III



CATEGORY: III



EN388:2016



4101X

EN374-1  
TYPE A



JKLOPT

EN374-5



VIRUS



## Properties

Chemical protection glove in premium grade nitrile rubber with excellent resistance against fats, aromatic and petroleum based solvents. Raised diamond pattern in the palm for increased grip in both wet and oily environments. Cotton flocklined interior for comfort. Food handling approved. Length (mm): 330 +/- 10, Thickness (mm): 0.40 +/- 0.03

## Material information

Length (mm): 330 +/- 10, Thickness (mm): 0.40 +/- 0.03, Material: Nitrile

## Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance  
cut resistance  
tear resistance  
puncture resistance  
extended cut resistance  
impact protection (optional)