

PRODUCT DATA SHEET



Fireman glove Spark

Art no: HGS-7923



HySafety



Art no:	HGS-7923
Size:	8-11
Materials:	Cow split leather, Kevlar, PU membrane
Packaging:	1/12
Standard:	EN420, EN388:2016, EN659
Category:	III



CATEGORY: III



EN388:2016



4244X

EN659



A1/AC



Kevlar

Properties

Heat resistant protective gloves for fire and rescue services and industries with requirements for heat and fire protection. Sewn in specially treated, flame retardant and thick cowhide split for the entire glove. Extra reinforcements in the grip for increased durability. Liner with insulating Kevlar® with a moulded membrane to make the glove wind and waterproof. Elastic seams for the wrist. Snug knitted cuff in double layered Kevlar® with a sturdy pull tab. All seams in durable and heat resistant Kevlar®.

Material information

The gloves are sewn in flame retardant cow split leather with Kevlar® thread. Kevlar® liner with a PU membrane. Cuff in knitted Kevlar®.

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se