

## Hyperguard

Art no: HV-NJ3150



Art no:	HV-NJ3150
Size:	7-12
Materials:	HPPE, Steel, Glass Fiber, Basalt, Nitrile
Packaging:	12/120
Standard:	EN420, EN388:2016
Category:	II



EN420



CATEGORY: II

EN388:2016



4X42D



## Properties

Thin and seamless cut resistant glove (Level D) in a HPPE mix. Reduces the risk of injury when in contact with materials with sharp edges, like glass and tiles. Equipped with a micro foam nitrile coating in the palm and over the fingertips. Butadiene free. The glove is abrasion resistant, oil resistant with an excellent grip in dry, wet or oily conditions. Very comfortable glove with great breathability and firm fit.

## Material information

Seamless knit cutter glove (Level D). Microfoamad nitrile coating in the inner hand.

## Technical facts: Intermediate design (category II)

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance —  
 cut resistance —  
 tear resistance —  
 puncture resistance —  
 extended cut resistance —  
 impact protection (optional) —

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.