

# PRODUCT DATA SHEET



## 26500V Class 3 insulated

Art no: NX-MOU-Q41Y



Art no:	NX-MOU-Q41Y
Size:	9-12
Materials:	Latex
Packaging:	1/6
Standard:	EN60903
Category:	III



CATEGORY: III

EN60903



Class 3 RC



## Properties

Insulating gloves with high durability for work with high voltage tasks. Made from premium latex using environmentally friendly water based production processes. Apart from the dielectric properties this manufacturing process makes the glove more flexible with higher dexterity. Must be tested regularly before use. Each glove is marked with the manufacturer testing date, along with a unique serial number for each individual glove. Straight cuff. Approximately 36cm long.

## Material information

100% natural latex, using environmentally friendly water based production processes

## Technical facts:

For high voltage risks, all gloves must be tested according to European standard EN60903:2003 testing methods and certified by a notified body. The testing is done for electrical resistance and optional special protection properties. The gloves are classified (from lowest 00 to highest 4) based on the maximum AC use of voltage shown in the table below. Special properties is indicated (if applicable) in designated alphabet shown below. Evaluate the importance of each of the properties and how it applies to you as a user.

Class	Max AC Use Voltage, V
00	500
0	1000
1	7500
2	17000
3	26500
4	36000
Property	Resistant to
A	Acid
H	Oil
Z	Ozone
R	Acid, Oil, Ozone
C	Extremely Low Temp

How to read the pictogram:

EN60903:2003



Class a b

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se