

# PRODUCT DATA SHEET



## Aquaguard Hyperguard

Art no: HV-LKX3150



Art no:	HV-LKX3150
Size:	8-12
Materials:	HPPE, Steel, Glass Fiber, Basalt, Latex
Packaging:	12/120
Standard:	EN420, EN388:2016
Category:	II



EN420



CATEGORY: II

EN388:2016



3X43D



## Properties

Waterproof knitted cut resistant glove in HPPE (Level D) in a HPPE mix. Double latex coating makes the glove waterproof and additional insulation properties. Butadiene free. Outer layer in Sandy Grip technology with a fantastic grip in dry, wet and oily conditions. Fully coated thumb for additional durability. Suitable for wet environments with risks for cuts and high requirements on a safe grip and long term usage.

## Material information

Knitted waterproof cut resistant glove in HPPE with superior fit and comfort even for use over long time. Cut protection (level D). Double latex coating makes the glove waterproof with additional insulation properties.

## Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance  
cut resistance  
tear resistance  
puncture resistance  
extended cut resistance  
impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se