PRODUCT DATA SHEET

Breathfit Thermo

Art no: HV-NXC970

Art no:	HV-NXC970
Size:	8-12
Materials:	Nitrile, polyester, acrylic
Packaging:	12/120
Standard:	EN420, EN388:2016, EN511
Category:	II

CATEGORY: II

EN388:2016 4231X

EN511:2006 X2X

Properties

Knitted winterglove in 13 gauge polyester with superior fit and comfort even for use over long time. Equipped with a soft and warm 10 gauge acrylic liner brushed on the inside for increased thermal insulation and comfort.
Nitrile coating with Sandy grip technology in the palm, over the full thumb and over the fingertips.
The glove is abrasion resistant, oil resistant with an excellent grip in dry or oily conditions. Very comfortable glove with great breathability and firm fit.

Material information

Knitted winterglove in 13 gauge polyester with superior fit and comfort even for use use over long time. Equipped with a soft and warm 10 gauge acrylic liner brushed on the inside for increased thermal insulation and comfort.

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resist- ance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016

a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)

Soft Touch AB
Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden
Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se