

## Ecotouch

Art no: HV-SE500



Art no:	HV-SE500
Size:	6/XS-12/3XL
Materials:	Nylon, Water-based PU
Packaging:	12/120
Standard:	EN ISO 21420:2020, EN388:2016
Category:	II



CATEGORY: II

EN388:2016



4131X



## Properties

Knitted white precision glove in nylon. The glove is thin and flexible with a great fit and tactile sensitivity. White water-based PU coating for a very good and firm grip. Butadiene and DMF free. The ergonomic design of the glove give advantages such as comfort and less hand fatigue.

## Material information

Knitted in 15 gauge nylon with water-based polyurethane coating.

## Technical facts: Intermediate design (category II)

How to read the pictogram:

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

EN388:2016



a b c d e f

abrasion resistance —┐  
cut resistance —┐  
tear resistance —┐  
puncture resistance —┐  
extended cut resistance —┐  
impact protection (optional) —┐