

PRODUCT DATA SHEET



Gentle Touch Black

Art no: RX-60BLK



Rubberex™



Art no:	RX-60BLK
Size:	S-XXL
Materials:	Nitrile
Packaging:	S-XL: 1 (100 pcs)/10 (1000 pcs) XXL: 1 (90 pcs)/10 (900 pcs)
Standard:	EN420, EN374-1:2016, EN374-5:2016
Category:	III



CATEGORY: III



EN420

EN374-1
TYPE B



KJTO

EN374-5



VIRUS



AQL

1.5%

Properties

Light weight disposable gloves in black nitrile with high flexibility and durability. Silicone and powder free. Ergonomically designed for perfect fit and higher sensitivity. Micro textured finishing for finger-tips and palm for improved grip and control. Approved for food stuff handling. Recommended for individuals with latex protein allergies. Length (mm): 240 +/- 10, Thickness (mm): 0.10 +/- 0.03, Weight (g) per pair: 6.0 +/- 0.2

Material information

Made from 100% nitrile. Length (mm): 240 +/- 10, Thickness (mm): 0.10 +/- 0.03, Weight (g) per pair: 6.0 +/- 0.2

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se