

Skydd 101

Art no:SCX-101



Art no:	SCX-101
Size:	6-11
Materials:	Nylon/lycra, nitrile
Packaging:	12/144
Standard:	EN420, EN388:2016
Category:	II



CATEGORY: II



EN388:2016



4121X



Properties

Seamless knitted glove sewn in nylon/lycra and coated in micro foamed nitrile in the palm and over the fingertips. The glove provides excellent grip and can be used for all types of precision work. The gloves are silicone free, solvent free and leave no fingerprints.

Material information

The glove is knitted with a 13 Gauge machine which means 13 stitches per inch. The thread is in nylon/ lycra and coated in micro foamed nitrile in the palm and over the fingertips formula so called Micro Foam. This technique is 100% water based.

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)