PRODUCT DATA SHEET



Hades Art no: C-1000











| Art no: | C-1000 |
|------------|---|
| Size: | 8-12 |
| Material: | Cowsplit, cowgrain, EVA foam, polyester/cotton Kevlar® lining, Kevlar® thread |
| Packaging: | 6/36 |
| Standard: | EN ISO 21420:2020, EN12477:2001, EN388:2019, EN407:2020 |
| Category: | II |















413X4>

Properties

Robust welding glove with cut protection made from durable yet flexible premium cowgrain leather, with grip reinforcements in cow split. Upper back and 15 cm long cuff made of cowsplit. Impact protection with 4mm EVA foam over the knuckles. Lined with a brushed Kevlar® liner inside the glove providing cut-resistance level D. Polyester/cotton liner in the cuff. The glove is stitched with strong, heat-resistant Kevlar® thread with double seams in exposed areas. An elastic seam around the wrist ensures the glove fits better and more securely on the hand.

Material information

The gloves are sewn in cowgrain and cowsplit leather. 4 mm EVA foam over the knuckles. Liner in the glove made with Kevlar®. Liner in the cuff made with polyester/cotton. All seams in Kevlar® thread.

How to read the pictogram:

EN388:2016

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resist- ance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

