PRODUCT DATA SHEET



Dionysos Art no: C-1400





Art no:	C-1400
Size:	8-12
Material:	Cowsplit, cowgrain, polyester/cotton Kevlar® lining, Kevlar® thread
Packaging:	6/36
Standard:	EN ISO 21420:2020, EN12477:2001, EN388:2019, EN407:2020
Category:	II







Properties


Robust welding glove with cut protection made from durable yet flexible premium cowgrain leather. Flexible grip reinforcements, upper hand and 15 cm long cuff made of cowsplit. Cuff with integrated pull tab. Artery protection made with cow grain. Lined with a brushed Kevlar® liner inside the glove providing cut-resistance level D. Polyester/cotton liner in the cuff. The glove is stitched with strong, heat-resistant Kevlar® thread with double seams in exposed areas. Ergonomic design with wing thumb.

Material information

The gloves are sewn in cowgrain and cowsplit leather. Liner in the glove made with Kevlar®. Liner in the cuff made with polyester/cotton. All seams in Kevlar® thread.

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resist- ance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



How to read the pictogram:

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se