# **PRODUCT DATA SHEET**



# Eros Art no: GV-1800











| Art no:    | GV-1800   |
|------------|---|
| Size:      | 8-12  |
| Material:  | Goatgrain, Goatsuede,<br>Cowsplit, Thinsulate® 40g,<br>Kevlar® thread     |
| Packaging: | 6/36  |
| Standard:  | EN ISO 21420:2020,<br>EN511:2007, EN12477:2001,<br>EN388:2019, EN407:2020 |
| Category:  | II  |





EN12477+A1 TYPE B



41224













## **Properties**

Winter welding glove with certified protection against cold. Made from treated goatgrain leather making the glove waterrepellent. Reinforced with double layer goatgrain leather for the index, pinky finger and the grip. Extra reinforced inside the palm with goatsuede for improved durability. Cuff in cowsplit. Sturdy elastic seam over the wrist for a safer fit. All seams in strong and heat resistant Kevlar® thread with double seams in exposed areas. Inside the glove is a Thinsulate™ 40g liner. The liner in combation with the certified protection against cold makes Soft Touch® Eros the ultimate winter welding glove.

### Material information

The gloves are sewn in goatgrain, goatsuede and cowsplit leather. Liner made with Thinsulate® 40g. All seams in Kevlar® thread.

How to read the pictogram:

EN388:2016

### Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resist- ance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

