

PRODUCT DATA SHEET



Mechabl

Art no: HV-A-3132B



NXG



Art no:	HV-A-3132B
Size:	6-12
Material:	Polyester, PU
Packaging:	12/120
Standard:	EN ISO 21420:2020, EN388:2016
Category:	II



CAT: II



EN388



3131X



Properties

Thin and extremely light knitted glove in black polyester. Very comfortable even at all day use. Thin black PU coating in the palm and up over the fingertips with high abrasion resistance. Butadiene free. The coating gives a good grip and excellent tactile sensitivity for precision work.

Material information

The glove is knitted with a 13 Gauge machine which means 13 stitches per inch. The thread is in polyester and coated in PU in the palm and over the fingers.

How to read the pictogram:

Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



a b c d e f

Abrasion resistance —
Cut resistance —
Tear resistance —
Puncture resistance —
Extended cut resistance —
Impact protection (optional) —

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se