

# PRODUCT DATA SHEET



## Oiltouch

Art no: HV-G-5240



Art no:	HV-G-5240
Size:	7-12
Material:	Nylon, Nitrile
Packaging:	12/120
Standard:	EN ISO 21420:2020, EN388:2016, EN407:2020,
Category:	II



CAT: II

EN388

EN407



4121X

X1XXXX



STANDARD  
100



## Properties

Knitted waterproof glove in nylon with superior fit and comfort even for long time use. Double nitrile coating makes the glove waterproof with excellent oil-resistant features. Butadiene free. Outer layer in a foamed nitrile coating with a great grip in dry, wet and oily conditions. Extremely light glove suitable for wet and oily environments with high requirements on a safe grip and long term usage.

## Material information

Knitted waterproof glove in 15g nylon with double nitrile coating in the inner hand.

How to read the pictogram:

## Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



a b c d e f

Abrasion resistance  
Cut resistance  
Tear resistance  
Puncture resistance  
Extended cut resistance  
Impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se