

PRODUCT DATA SHEET



ErgoTec® Plus Orange

Art no: ADF-844OR



| | |
|------------|--|
| Art no: | ADF-844OR |
| Size: | 6-12 |
| Material: | Nylon/lycra, Micro foamed nitrile |
| Packaging: | 12/144 |
| Standard: | EN ISO 21420:2020, EN388:2016, EN407:2020 |
| Category: | II |



CAT: II



EN388



4121X

EN407



X1XXXX



Properties

Seamless knitted orange glove sewn in nylon/lycra and coated in micro foamed nitrile in the palm and over the fingertips. The glove is equipped with orange nitrile dots in the whole palm to provide durability and dampening and can be used for all types of precision work. The gloves are silicone free, solvent free and leave no fingerprints.

Material information

The glove is knitted with a 15 Gauge machine which means 15 stitches per inch. The thread is in nylon/lycra and coated in micro foamed nitrile in the palm, over the fingers and over the knuckles. Nitrile dots in the whole palm. This technique is 100% water based.

How to read the pictogram:

Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



a b c d e f

Abrasion resistance
Cut resistance
Tear resistance
Puncture resistance
Extended cut resistance
Impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se