

PRODUCT DATA SHEET



Air 5230

Art no: HV-A-5230



NXG



Art no:	HV-A-5230
Size:	7-12
Material:	Nylon/Spandex, Microfoam Nitrile
Packaging:	12/120
Standard:	EN ISO 21420:2020, EN388:2016, EN407:2020
Category:	II



CAT: II



EN388



4131A

EN407



X1XXXX



STANDARD
100



Properties

Seamless knitted glove sewn in nylon/spandex and coated in hydrofoamed nitrile in the palm and over the fingertips. The glove is durable, oil resistant and provides excellent grip in dry and oily environments. The gloves are silicone free, chrome free, solvent free and leave no fingerprints.

Material information

The glove is knitted with a 15 Gauge machine which means 15 stitches per inch. The thread is in nylon/spandex and coated in hydrofoamed nitrile in the palm and over the fingers.

How to read the pictogram:

Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



a b c d e f

Abrasion resistance
Cut resistance
Tear resistance
Puncture resistance
Extended cut resistance
Impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se