

# PRODUCT DATA SHEET



## Cut Pro 8131

Art no: HV-C-8131



Art no:	HV-C-8131
Size:	6-12
Material:	Nylon/NXG UCT™/Spandex, Nitrile
Packaging:	12/120
Standard:	EN ISO 21420:2020, EN388:2016
Category:	II



EN388



4X42C



STANDARD 100



CAT: II

## Properties

Knitted precision glove with cut-resistance (Level C) in nylon/spandex and UHMWPE. The glove is extremely thin and flexible with a great fit and exceptional tactile sensitivity. Black foamed nitrile coating for a firm grip and great oil-resistance. Touch screen compatible so you can use your phone without removing the gloves. Reinforced thumb crotch improves durability in high-wear areas. Butadiene free. The ergonomic design of the glove give advantages such as comfort and less hand fatigue.

## Material information

The glove is knitted with a 18 Gauge machine which means 18 stitches per inch. The thread is in Nylon/UHMWPE/Spandex and coated in foamed nitrile in the palm and over the fingers.

How to read the pictogram:

## Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



a b c d e f

Abrasion resistance  
Cut resistance  
Tear resistance  
Puncture resistance  
Extended cut resistance  
Impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se