

PRODUCT DATA SHEET



Joka Nordic

Art no: JKS-NORD



Art no:	JKS-NORD
Size:	10-12
Material:	BIOVYN™ vinyl, cotton, acrylic
Packaging:	10/60
Standard:	EN 420:2003+A1:2009, EN ISO 374-1:2016 Type A, EN 374-2:2014, EN ISO 374-5:2016, EN 16523-1:2015, EN 388:2016, EN 511:2006, EN ISO 4675:2017, EN ISO 7854:1997 Method A, EN ISO 2286-3:1998
Category:	III



0403



CAT: III

EN374-1



KLMPST

EN374-5



EN388



2121X

EN511



321



Properties

Joka Nordic is a flexible, warm and durable vinyl coated finger glove for cold environments working with for example oil and chemicals.

The smooth TopGrip-surface is made from BIOVYN™-vinyl that remain flexible even at -50°C. The glove has a liner in 100% cotton as well as a detachable synthetic fur liner. Washable.

The vinyl in this glove is made from fossil free BIOVYN™-vinyl. Renewable BIOVYN™ reduce the carbon dioxide footprint up to 74% compared to vinyl made from traditional fossil fuels. Biovinyl products have the exact same properties as conventional fossil vinyl products making them very durable with an excellent protection against chemicals and mechanical abrasion as well as extreme weather conditions.

Material information

The gloves are made of vinyl, with liners made from 100% cotton and acrylic fur.

How to read the pictogram:

Technical facts: Intermediate design (category II)

EN388:2016

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.



a b c d e f

Abrasion resistance	—
Cut resistance	—
Tear resistance	—
Puncture resistance	—
Extended cut resistance	—
Impact protection (optional)	—

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se